

## ENGINEERING DATA SHEET

|                                                                                                                                                                                                                     |     |                |     |                        |     |                                           |     |               |            |        |             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------------|-----|------------------------|-----|-------------------------------------------|-----|---------------|------------|--------|-------------|
| Long Description                                                                                                                                                                                                    |     |                |     | Description            |     | POS TRANS PROX 4-20MA HART<br>ATEX EXD SS |     | Part #        | 10103790   | Rev    | B           |
| ROTARY POSITION TRANSMITTER, PROXIMITY MARK 4 THRU SHAFT MODEL, 4-20 MA W/ HART SIGNAL, NO LIMIT SWITCHES, 24 VDC DIRECT DRIVE, STAINLESS STEEL HOUSING, 1 X 3/4" NPT ENTRY, ATEX II 2 G EEX D IIC T6 (FLAME PROOF) |     |                |     |                        |     |                                           |     | Drawing #     |            | Status | Released    |
|                                                                                                                                                                                                                     |     |                |     |                        |     |                                           |     | Design File # | SDF 140563 | ECN    | 06675       |
| Weight (lbs)                                                                                                                                                                                                        | N/A | Customer       |     |                        |     |                                           |     | Created By    | C WILSON   | Date   | 11-FEB-2015 |
| Industry Specification                                                                                                                                                                                              | N/A | PSL/QSL        | N/A | Temperature Rating     | N/A | Material Class                            | N/A | Revised By    | B SINGH    | Date   | 26-NOV-2019 |
| API Monogram                                                                                                                                                                                                        | No  | MOC Controlled | No  | Temperature Range (°F) | N/A |                                           |     | Approved By   | O ENANGA   | Date   | 26-NOV-2019 |

| Quality Specifications |                      |
|------------------------|----------------------|
| Specification          | Description          |
| QS-1000                | JOB LOT TRACEABILITY |
| Notes                  |                      |

| Process Specifications |                                                  |
|------------------------|--------------------------------------------------|
| Specification          | Description                                      |
| PS-1000                | COMPONENT MARKING & IDENTIFICATION               |
| Notes                  | PS-1000: TAG PART / CONTAINER:<br>10103790 REV B |

|               |                                                                     |
|---------------|---------------------------------------------------------------------|
| General Notes | PROXIMITY P/N: 49OE6-B<br>INCLUDES: 103-046 (WINDOW), 115-011 (POT) |
|---------------|---------------------------------------------------------------------|