

Hazardous Area Analog Telephones - Outdoor - Div. 2

By GAI-Tronics
Catalog # 351-001

Hazardous Area Analog Telephones - Outdoor - Div. 2



Features

- Hazardous Area approved for: Class I, Division 2, Groups A, B, C, D
- Class II, Division 2, Groups F and G
- Class III
- Economical Communications for Division 2 Areas
- Indoor and Outdoor Models
- Anti-corrosive Enclosures
- Hearing Aid Compatible (HAC) with Pushbutton Volume Control
- Hytel Coiled Cord or Straight Armored Cord
- Sealed Chrome-plated Keypad
- Extreme Operating Temperature Range
- Conformal Coating on PCBA

Specifications

| | |
|---------------------|---|
| Hazardous Rating(s) | <ul style="list-style-type: none"> • Class I, Division 2, Groups A, B, C, D • Class II, Division 2, Groups F & G • Class III, Division 2 |
| Nema Rating | NEMA 3R |
| Certification | <ul style="list-style-type: none"> • UL • CSA • IC |
| Weather Rating | Type 3R |

Configuration

Mount location

Surface-Mount

Current

Signal
Input Voltage

Phone Line
Phone Line

Dimensions

| | |
|---------------------|---------------------------|
| Width | 13.2 in |
| Weight | 8.2 lb. |
| Height | 9.4 in |
| Dimensions Shipping | 16.5 x 16.0 x 10.0 |
| Length | 7.4 in |
| Dimensions | 7.4 in x 13.2 in x 9.4 in |

General

| | |
|----------------|-----------------|
| Type | Outdoor Use |
| Signal Type | Analog |
| Material type | Engrd. Plastic |
| Specifications | UL/CSA, FCC, IC |
| Color | Blue |

Operational

| | |
|----------------------|---------|
| Connectivity Options | Analog |
| Output Level Ringer | 84 @ 1M |

Product Assets

[Installation Manual \[English\]](#)