

ROTEX AUTOMATION LIMITED

Address : 987/11, GIDC Makarpura, Vadodara - 390 010, India.

Website : www.rotexautomation.com

E-mail : info@rotexautomation.com

*Engineering For The Future***DATASHEET**

Type of Valve	: 5/2 Internal Pilot Operated Spring Return Single Solenoid Valve
Ordering Code	: 51400-6-2G+III-230V-50Hz-25-H
Item Code	:
Port Connection	: 1/4" BSP(F)
Orifice Size (mm)	: 6 mm
Flow Factor (kv)	: 12 LPM
Body Material	: Aluminium Hard Anodised
Manual Override	: Manual Override Provided Push to operate momentarily, for stayput using Screw Driver push & turn CW to operate valve
Seat Seal Material	: NBR
Media	: Air;
Main Pressure	: 2 - 10 bar
Media Temp Range	: -25°C to +75°C
Type of Solenoid	: DIN plug Solenoid, DIN 43650A PG9 Cable Entry, IP67
Size of Coil	: III
Enclosure Material	: CRCA - Chrome Plated
Voltage	: 230V 50Hz/ 240V 60Hz (-10%, +10%)
Power of Coil	: 6 W
Insulation Class	: Class H
Approval	: Weather proof
Coil Certificate nr.	: KLPL/BTG/18/09-88
Marking	: Weather Proof IP67
Created By: Raj	Print Date And Time: 03/06/2025 19:53
This is System Generated Report	

Reg. Office : 987/11, GIDC, Makarpura, Vadodara – 390 010, India.

Jurisdiction : Vadodara, Gujarat, India.

CIN NO. : U29259GJ1983PLC005831 GST NO. : 24AABCR0011J1Z0

Phone : +91 265 617 4100

+91 265 263 8136

Fax : +91 265 263 1352