

S - 1/2" metric 12-point sockets



Standards:

**NF ISO 2725-1, NF ISO 1711-1,
ISO 2725-1, ISO 1711-1, DIN
3124, ASME B107.5**

Description:

- OGV® profile: more powerful tightening, preserves fasteners.
- Finish: bright chrome.
- Supplied on metal rack. Ref S.40E (8 --> 16 mm) and Ref S.41E (17 --> 24 mm).

	A [mm]	Diameter [mm]	Diameter D1 [mm]	Length L [mm]	Length L1 [mm]	12-Point [mm]	Weight [g]
S.10	10	22.8				12.0	50.0
S.10PB	10	22.8				12.0	50.0
S.11	11.0	22.8	16.5	36.0	9.0	12.0	50.0
S.11PB	11.0	22.8	16.5	36.0	9.0	12.0	50.0
S.12	12.0	22.8	17.8	36.0	9.5	12.0	50.0
S.13	13.0	22.8	18.9	36.0	10.4	12.0	50.0
S.13PB	13.0	22.8	18.9	36.0	10.4	12.0	50.0
S.14	14.0	22.8	20.2	36.0	10.5	12.0	55.0
S.14PB	14.0	22.8	20.2	36.0	10.5	12.0	55.0
S.15	15.0	22.8	21.4	36.0	12.0	12.0	55.0
S.15PB	15.0	22.8	21.4	36.0	12.0	12.0	55.0
S.16	16.0	21.6	22.6	36.0	12.0	12.0	55.0
S.16PB	16.0	21.6	22.6	36.0	12.0	12.0	55.0
S.17	17.0	23.1	24.1	36.0	13.0	12.0	65.0
S.17PB	17.0	23.1	24.1	36.0	13.0	12.0	65.0
S.18	18.0	23.4	25.4	36.0	13.0	12.0	70.0
S.18PB	18.0	23.4	25.4	36.0	13.0	12.0	70.0
S.19	19.0	24.6	26.6	36.0	14.0	12.0	75.0
S.19PB	19.0	24.6	26.6	36.0	14.0	12.0	75.0
S.20	20.0	25.4	27.4	36.0	14.0	12.0	80.0
S.20PB	20.0	25.4	27.4	36.0	14.0	12.0	80.0
S.21	21.0	25.1	29.1	38.0	16.0	12.0	85.0
S.21PB	21.0	25.1	29.1	38.0	16.0	12.0	85.0
S.22	22.0	26.4	30.4	38.0	16.5	12.0	95.0
S.22PB	22.0	26.4	30.4	38.0	16.5	12.0	95.0
S.23	23.0	27.6	31.6	38.0	16.5	12.0	105.0
S.23PB	23.0	27.6	31.6	38.0	16.5	12.0	105.0
S.24	24.0	28.7	32.7	38.0	16.5	12.0	115.0

S.24PB	24.0	28.7	32.7	38.0	16.5	12.0	115.0
S.25	25.0	27.7	34.1	38.0	16.5	12.0	125.0
S.25PB	25.0	27.7	34.1	38.0	16.5	12.0	125.0
S.26	26.0	29.0	35.4	38.0	16.5	12.0	135.0
S.26PB	26.0	29.0	35.4	38.0	16.5	12.0	135.0
S.27	27.0	29.2	36.6	44.0	19.0	12.0	160.0
S.27PB	27.0	29.2	36.6	44.0	19.0	12.0	160.0
S.28	28.0	30.5	37.9	44.0	20.0	12.0	175.0
S.28PB	28.0	30.5	37.9	44.0	20.0	12.0	175.0
S.29	29.0	31.3	38.7	44.0	20.0	12.0	190.0
S.29PB	29.0	31.3	38.7	44.0	20.0	12.0	190.0
S.30	30.0	33.0	40.4	44.0	20.0	12.0	200.0
S.30PB	30.0	33.0	40.4	44.0	20.0	12.0	200.0
S.31	31.0	34.2	41.6	44.0	20.0	12.0	205.0
S.32	32.0	35.1	42.5	44.0	20.0	12.0	210.0
S.32PB	32.0	35.1	42.5	44.0	20.0	12.0	210.0
S.34	34.0	37.5	44.9	44.0	20.0	12.0	240.0
S.8	8.0	22.8	13.1	36.0	6.5	12.0	45.0
S.8PB	8.0	22.8	13.1	36.0	6.5	12.0	45.0
S.9	9.0	22.8	13.8	36.0	6.5	12.0	50.0
S.9PB	9.0	22.8	13.8	36.0	6.5	12.0	50.0