


Sand Blasting Hose



Sandblast 12 bar (174 psi)

SPECIFICATIONS:

TUBE	: Black conductive NR - abrasion resistant
REINFORCEMENT	: High tensile textile cord
COVER	: Black conductive SBR/NR - abrasion and ozone resistant - pin pricked
USE	: Abrasive material blasting
SAFETY FACTOR	: 2.5:1
TEMPERATURE	: -30°C + 80°C (-22°F + 176°F)

							
mm	inch	mm	inch	bar	psi	kg/m	lb/ft
13	1/2	27	1.06	12	174	0.560	0.380
19	3/4	33	1.30	12	174	0.710	0.480
19	3/4	35	1.38	12	174	0.830	0.560
25	1	39	1.53	12	174	0.870	0.585
32	1 1/4	48	1.89	12	174	1.240	0.835
38	1 1/2	55	2.17	12	174	1.650	1.110
40	1 9/16	60	2.36	12	174	1.930	1.300
51	2	71	2.80	12	174	2.400	1.615

19	3/4	38	1.50	12	174	1.000	0.675
25	1	48	1.89	12	174	1.540	1.035
32	1 1/4	55	2.17	12	174	1.830	1.230
38	1 1/2	60	2.36	12	174	2.080	1.400
51	2	73	2.87	12	174	2.630	1.770

Sand Blasting Hose



Part No.	Description
0032-242/S-AL	Speedo Blast Hose 1/2" x 20m (ID 13 x OD 27mm)
0032-244/S-AL	Speedo Blast Hose 1/2" x 40m (ID 13 x OD 27mm)
0032-262/S-AL	Speedo Blast Hose 1" x 20m (ID 25 x OD 39mm)
0032-264/S-AL	Speedo Blast Hose 1" x 40m (ID 25 x OD 39mm)
0032-272/S-AL	Speedo Blast Hose 1-1/4" x 20m (ID 32 x OD 48mm)
0032-274/S-AL	Speedo Blast Hose 1-1/4" x 40m (ID 32 x OD 48mm)

SPEEDO MARINE (PTE) LTD | ADDRESS: 11 TUAS LINK 2, SINGAPORE 638559

TEL: +65 6863 1998 | FAX: +65 6863 1667 | EMAIL: enquiry@speedo.com.sg | WEBSITE: www.speedo.com.sg

Ver. 270217. All written and visual data contained in this document are based on the latest product information available at the time of publication. Speedo Marine (Pte) Ltd reserves the right to make changes at any time without notice. All other brand names or marks are used for identification purposes and are trademarks of their respective owners.