



[PRODUCTS](#) > [EXTENSION LADDERS](#) > [D6200-2 SERIES](#) > 32FT TYPE IA
FIBERGLASS D-RUNG EXTENSION LADDER D6232-2

32FT TYPE IA FIBERGLASS D-RUNG EXTENSION LADDER D6232-2

★★★★☆ 4.0 | 1 Review

1 out of 1 (100%) reviewers recommend this product

24 questions and 25 answers for this product

[Write a review](#)

[Ask a question](#)





VIDEOS



BUY NOW

Style: Multi-Section

Size: 32ft

Type: Type IA Duty Rating

[🔗 Resources](#) [🔗 Compatible Accessories](#)

The D6232-2 Fiberglass Two-Section 32-foot Extension Ladder has non-conductive rails making this ladder ideal for working near electricity. With a duty rating of 300 pounds, the ladder is durable and long lasting. The exclusive Alflo® rung joint means Twist-Proof® performance on the job. The Traction-Tred® D rungs are slip-resistant and the side rails are interlocking. The dual action feet are for use on hard or penetrable surfaces and swivel easily. The base and fly sections separate easily to use the base section as a single ladder. The durable rail shield bracket and shoe help protect the bottom of the rail. The fly section rails are pre-pierced at the top for easy field installation of accessories.

FEATURES

- Exclusive Alflo® rung joint means Twist-Proof® performance

- 1.63-inch slip-resistant Traction-Tred® D-rungs
- Smooth operating pulley with polypropylene rope
- Interlocking side rails, with internal rail guides on bottom of fly section, securely connect rails
- External guides at top of base section securely interlock rails
- Heavy-duty extruded rung locks are spring loaded to operate smoothly
- Pre-pierced holes for easy field installation of accessories
- Base and fly separate easily to use base section as single ladder
- Combination rail shield bracket and shoe with SHU-LOK® and slip-resistant pad
- Molded rung braces on bottom step for increased durability
- Mar-resistant molded end caps

SPECIFICATIONS

DETAILS

Style	Multi-Section
Size	32ft
Type	Type IA Duty Rating
Load Capacity (lb)	300
Material	Fiberglass
Certifications	ANSI A14.5-2007, OSHA
Werner Benefit	Exclusive Alflo® rung joint means Twist-Proof® performance
Unique Features	Works Around Electricity
Color	Orange
Foot Design	Shu-Lok ®, and spur plate
Max. Load	300lb
Number of Sections	2
Sections x Rungs	2 x 16
Show Less	

Country of Origin	Mexico
UPC	051751019155

DIMENSIONS

Average Reach Height Extension Ladder (ft)	31ft
Max. Open Extended Height (ft)	29ft 1in
Approx. Product Length (in)	192
Approx. Product Width (in)	19
Approx. Product Height (in)	6.31
Approx. Product Weight (lb)	71.5
Approx. Shipping Length (in)	192
Approx. Shipping Width (in)	19
Approx. Shipping Height (in)	6.9
Approx. Shipping Weight (lb)	71.5
Approx. Product Length (ft)	16
Flange Dimension (in)	1.19in
Fly Width	16in
Rails Dimension	3.31in
Steps/Rung Dimension	1.625in

RESOURCES

 [View D6200-2 Series Page](#)

 [Safety Inspection Form](#)