




ADAPTOR

Application

- Flameproof (Ex 'd') & Increased Safety (Ex 'e')
- Connection between cable entry devices and equipment having dis-similar threads.
- Male, Female threads : Metric to Metric, Metric to NPT, NPT to NPT, NPT to Metric
- Operating Temperature : -60°C to +100°C
- Materials : Brass / Brass with Nickel plated / Aluminum / Stainless Steel 316
- Ingress Protection : IP66
- Certificate No : Baseefa08 ATEX 0019X / IECEx BAS08.0008X.

TR-CU : 0338518



Male Thread (*)		Female Thread (*)																				METRIC "E"	
		METRIC										NPT											
			M16	M20	M25	M32	M40	M50	M63	M75	M80	M90	M100	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3" 3 1/2"	4"
METRIC			⊗	⊗	⊗								⊗	⊗									9
	M16			⊗	⊗	⊗							⊗	⊗									
	M20				⊗	⊗	⊗						⊗	⊗	⊗								
	M25					⊗	⊗	⊗						⊗	⊗	⊗							
	M32						⊗	⊗	⊗						⊗	⊗	⊗						
	M40							⊗	⊗	⊗						⊗	⊗	⊗					
	M50								⊗	⊗	⊗						⊗	⊗	⊗				10
	M63									⊗	⊗	⊗						⊗	⊗	⊗			
	M75										⊗	⊗	⊗						⊗	⊗	⊗	⊗	
	M80											⊗	⊗							⊗	⊗	⊗	
	M90													⊗							⊗	⊗	
M100																				⊗	⊗		
NPT	1/2"		⊗	⊗	⊗									⊗	⊗								
	3/4"				⊗	⊗	⊗								⊗	⊗							
	1"					⊗	⊗	⊗								⊗	⊗						
	1 1/4"						⊗	⊗	⊗								⊗	⊗					
	1 1/2"							⊗	⊗	⊗								⊗	⊗				
	2"								⊗	⊗	⊗	⊗							⊗	⊗			
	2 1/2"									⊗	⊗	⊗	⊗							⊗	⊗	⊗	
	3"										⊗	⊗	⊗								⊗	⊗	
	3 1/2"													⊗								⊗	
	4"																						

* PF Threads are available KGS Ex-proof certificate.

How to order

DAAD - M20 x N3/4"

- Female Thread
- Male Thread
- Dong-A Type Number



II 2GD Ex db II C Ex eb II C Extb II C IP66 Baseefa08ATEX0019X IECEx BAS08.0008X
DAAD-NxxMxx xx(M)x xx(F) 2011/03 DONG-A Bucheon KR CE1180