

Find device features by order code



Device details

Product name	Micropilot FMR51
Order code	FMR51-BBACBDBDA5AJJ+AAF4JAKIOUPBZ1
Product status	● Available



Configuration

Characteristic	Value	Description	TSP-No.
Approval:	BB	ATEX II 1/2G Ex ia IIC T6 Ga/Gb	-
Power Supply; Output:	A	2-wire; 4-20mA HART	-
Display, Operation:	C	SD02 4-line, push buttons + data backup function	-
Housing:	B	GT18 dual compartment, 316L	-
Electrical Connection:	D	Thread NPT1/2, IP66/68 NEMA4X/6P	-
Antenna:	BD	Horn 100mm/4"	-
Seal:	A5	FKM Viton GLT, -40...150oC/-40...302oF	-
Process Connection:	AJJ	NPS 6" Cl.150 RF, 316/316L flange ASME B16.5	-
>Additional Operation Language:	AA	English	-
>Calibration:	F4	5-point linearity protocol	-
>>Test, Certificate:	JA	3.1 Material certificate, wetted metallic parts, EN10204-3.1 inspection certificate	-
	KI	PMI test (XRF), internal procedure, wetted metallic parts, inspection certificate	-
>>Accessory Mounted:	OU mm antenna extension, 316L	-
>>Accessory Enclosed:	PB	Weather protection cover	-
>>Marking:	Z1	Tagging (TAG), see additional spec.	-

Find device features by order code

