


FED. MFG. CODE 91929





SERIES CHT 2

1,13 Kg	2.49 LB
---------	---------



- 1 - EXPLOSION PROOF-UNDERWRITERS LAB INC LISTING
FOR HAZARDOUS LOCATIONS CLASS I, GROUPS C AND D; CLASS II,
GROUPS E, F AND G
- 2 - ALUMINUM ENCLOSURE FINISHED WITH BLUE AND BLACK EPOXY
PAINT
- 3 - 6-32 UNC X 7,92 REF PAN HEAD TERMINAL SCREW AND LOCK-
WASHER (SEMS TERMI-LOX) (3 PER BASIC)
- 4 - CAMS MAY BE REPOSITIONED IN 7°20' INCREMENTS
- 5 - FOR USE IN TEMPERATURES UP TO 85° C
- 6 - UNIT PROVIDES NO SHAFT RESTORING FORCE, THE ACTUATING
DEVICE MUST CONTROL MOVEMENT OF SHAFT
- 7 - SEE (M) 7CX CHARTS 1 AND 2 FOR LEVER ACTUATORS

WEIGHT 1.13 Kg APPROX

CAT. LIST. 	DESCRIPTION 	ELECTRICAL DATA
(B)	1 BASIC; OPERATES CLOCKWISE & COUNTER CLOCKWISE	UL LISTED-FILE E14274 CODE L96 15A-125, 250 OR 480 VAC 1/8 HP-125 VAC; 1/4 HP-250 VAC 1/2 A-125 VDC; 1/4 A-250 VDC 
11CX12-	2 BASICS; EACH OPERATES CLOCK- WISE & COUNTER CLOCKWISE	
11CX12C	2 BASICS; EACH OPERATES CLOCK- WISE & COUNTER CLOCKWISE	
11CX15-	2 BASICS; 1 OPERATES CLOCKWISE ONLY; 1 OPERATES COUNTER CLOCK- WISE ONLY	
12CX11-	1 BASIC; OPERATES CLOCKWISE & COUNTER CLOCKWISE	UL LISTED-FILE E14274 CODE L23 20A-125, 250 OR 480 VAC 10A-125 VAC "L" 1HP-125 VAC; 2HP-250 VAC 1/2A-125 VDC; 1/4A-250 VDC 
12CX12-	2 BASICS; EACH OPERATES CLOCK- WISE & COUNTER CLOCKWISE	
12CX15-	2 BASICS; 1 OPERATES CLOCKWISE ONLY; 1 OPERATES COUNTER CLOCK- WISE ONLY	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Honeywell:

[11CX12](#) [11CX12C](#) [12CX12](#) [12CX15](#)