





Bulkhead SSK20



Version A

Version B

Version C

Version D

- Also available for gaseous media Type SSKK

Threads

*1 Compression ring assembly 08L/ 08S/ 12L according to ISO 8434-1 / DIN 2353

*2 JIC cone fitting according to SAE J514

*3 O-ring face sealing according to SAE J1453

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (CrVI-free)**

For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".

For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering FPM sealings replace "P" with "V".

For ordering EPDM sealings replace "P" with "E".

* Standard option for North America is FPM (Viton®).

Protection Cap

Standard material: Steel

For ordering the hexagonal protection cap version please add

"-SK" to the order code. (e.g. SKK20-P-SK-C6F)

For ordering the plastic protection cap version please add

"-KK" to the order code. (e.g. SKK20-P-KK-C6F)

For further information on materials, sealings or protection caps, please see page B4.

Note: Standard option version B without compression ring and nut.

Thread G	Dimensions (mm/in)		Version	Order Codes NBR	FPM* (Standard Option-North America)
	h	Hex			
M16	72 2.83	19 .75	A	SSK20-P-C6F	SSK20-V-C6F
M14 x 1,5*1	72 2.83	19 .75	B	SSK20/08L-P-C6F	SSK20/08L-V-C6F
M16 x 1,5*1	72 2.83	22 .87	B	SSK20/08S-P-C6F	SSK20/08S-V-C6F
M18 x 1,5*1	72 2.83	22 .87	B	SSK20/12L-P-C6F	SSK20/12L-V-C6F
7/16-20 UNF*2	66 2.60	17 .67	C	SSK20/J7/16UNF-MV-P-C6F	SSK20/J7/16UNF-MV-V-C6F
9/16-18 UNF*3	67 2.64	22 .87	D	SSK20-04-ORFS-P-C6F	SSK20-04-ORFS-V-C6F
11/16-16 UN*3	72 2.83	27 1.06	D	SSK20-06-ORFS-P-C6F	SSK20-06-ORFS-V-C6F
13/16-16 UNF*3	75 2.95	30 1.18	D	SSK20-08-ORFS-P-C6F	SSK20-08-ORFS-V-C6F