



3940-WM

Sandflex® Bi-Metal Sabre Sawblades for Wood and Metal

PRODUCT DETAILS

- The wood and metal blade family is designed for demanding cutting in wood with embedded nails but can also be used for thick metal materials
- Virtually unbreakable Sandflex® bi-metal blade for all materials and type of cut
- HSS toothing with 8% Cobalt
- Version 1: slope shaped (SL) bi-metal blades with precision ground teeth are a series of thicker blades with a narrow nose
- It accessible in narrow places but still rigid and has a higher resistance to fracturing and bending, allowing straighter cuts
- Version 2: standard (ST) bi-metal blades with coarse precision ground teeth are a series of flexible blades with standard body
- That makes it more flexible and easier to bend into position
- 0.9 mm to 1.9 mm thickness
- 4/6 TPI to 8/12 TPI
- 150 mm to 300 mm of length
- Packaging alternative 1: retail packed either in -2P = 2 blades or -5P = 5 blades per pack
- Packaging alternative 2: industrial pack, -10P = 10 blades or in big industrial pack -100P = 100 blades per box

Follow the Fish!



PRODUCT ATTRIBUTES

Product					
3940-150-4/6-SC-2P	150 mm	1.3 mm	4/6	SC	45 g
3940-150-4/6-SC-5P	150 mm	1.3 mm	4/6	SC	105 g
3940-150-4/6-SC-10P	150 mm	1.3 mm	4/6	SC	180 g
3940-150-5/8-SL-2P	150 mm	1.3 mm	5/8	SL	44 g
3940-150-5/8-SL-5P	150 mm	1.3 mm	5/8	SL	100 g
3940-150-5/8-SL-100P	150 mm	1.3 mm	5/8	SL	1688 g
3940-150-6-ST-2P	150 mm	0.9 mm	6	ST	60 g
3940-150-6-ST-5P	150 mm	0.9 mm	6	ST	140 g
3940-150-6-ST-10P	150 mm	0.9 mm	6	ST	150 g
3940-228-6-SL-2P	228 mm	1.3 mm	6	SL	64 g
3940-228-6-SL-5P	228 mm	1.3 mm	6	SL	160 g
3940-228-6-SL-10P	228 mm	1.3 mm	6	SL	330 g
3940-300-6-SL-2P	300 mm	1.3 mm	6	SL	110 g
3940-300-6-SL-5P	300 mm	1.3 mm	6	SL	255 g
3940-300-6-SL-10P	300 mm	1.3 mm	6	SL	460 g
3940-300-8/12-SL-2P	300 mm	1.3 mm	8/12	SL	104 g
3940-300-8/12-SL-5P	300 mm	1.3 mm	8/12	SL	260 g
3940-300-8/12-SL-10P	300 mm	1.3 mm	8/12	SL	465 g
3940-300-8/12-SL-100P	300 mm	1.3 mm	8/12	SL	4650 g

Follow the Fish!



Contact: info@bahco.com / www.bahco.com